



	804-2104	804-2108	804-2122	804-2114
<b>EAN</b>	7640125680010	7640125680034	7640125680188	7640125680164
<b>Model</b>	MB-4C	MB-8i	MB-2S	MB-4D
<b>Instrument type</b>	Sylvac capacitive probes	Inductive <sup>1</sup>	Heidenhain probes (11µmA/1VPP)	Digimatic
<b>Compatibility</b>	D300S & D400S			
<b>Dimensions (L x h x w) (mm)</b>	107x42x74	131x44x74	82x43x74	107x39x74
<b>Weight (kg)</b>	0.2	0.3	0.2	0.2
<b>Inputs</b>	4	8	2	4
<b>Case</b>	Anodized aluminium profile			
<b>Output data</b>	RS 485			



	804-2111	804-2107	804-2105	804-2130
EAN	7640125688856	7640125711424	7640125712216	7640125680201
Model	MB-1D	FMB-4i (fast version)	MB-4P	MB-IO
Instrument type	Digimatic	Inductive *	Probes P12D	PLC I/O
Compatibility	D300S & D400S			D300S, D400S & D70
Dimensions (L x h x w) (mm)	52x39x74	107x39x74	107x42x74	82x39x74
Weight (kg)	0.1	0.2		
Inputs	1	4		8
Case	Anodized aluminium profile			
Output data	RS 485			

\* Half-bridge



	804-2140	804-2160	804-2170	804-2180
<b>EAN</b>	7640125680218	7640125027716	7640125681215	7640125681239
<b>Model</b>	MB-PS	MB-RS	MB-TP	MB-BT
<b>Instrument type</b>	Power-Supply	Computer	Temperature sensor input PT100 and Thermocouple	Instruments with Bluetooth® wireless technology
<b>Compatibility</b>	D300S, D400S & D70		D300S, D400S & D70	
<b>Dimensions (L x h x w) (mm)</b>	52x42x74	82x39x74	52x51x74	52x39x74
<b>Weight (kg)</b>	0.2	0.2	0.1	0.1
<b>Inputs</b>	12-30 VDC	254	1 / 1	8
<b>Case</b>	Anodized aluminium profile			
<b>Output data</b>	RS 485			



	804-2190	804-2132	804-2133
EAN	7640125681246	7640125695533	7640125695496
Model	MB-AG	MB-NET	MB-RO
Instrument type	Plug gauges and Air gauges	Ethernet connector for server sending	Relay output
Compatibility	D400S & D70		
Dimensions (L x h x w) (mm)	52x64x74		
Weight (kg)	0.15		
Inputs	1		
Case	Anodized aluminium profile		
Output data	RS 485		